



Compact building protection.

We are offering the IFEX- CFFC as a standard version, but it can be adapted according upon customers wishes and requirements.

For example: depending on the existing infrastructure, a connection to an external water supply line could be realized.

Do not hesitate to contact us! It is a pleasure for us to advise you.

From preliminary design with modern 3-D-CAD-systems to the delivery of an operational system inclusive professional instruction we supply highest quality approved according to the latest standards.

Accurately adaption according to the existing installation situation in the building connected with an professional assembly of high quality components.

IFEX always has the adequate solution

TECHNICAL DATA *:

Dimensions (H x W x D):	1800 x 1300 x 400 mm
Water provision:	80 Liters in plastic tank (PE)
Press. air provision:	1 x 6 Liters/ 300 bar in steel cylinder
Cylinder valve:	With built in pressure gauge for provision control
Hose reel:	30 meters coaxial hose; manually operated
Extinguishing agent feeding pump:	230 V/ AC; 0,55 kW/ 1800 liters/ min. at 10 bar pressure
Extinguishing unit:	IFEX IP3 Impulse gun
Operating temperature:	+5°C to +40°C
Closure element:	Hinged door

OPTIONS:

Dimensions:	Special size on request
Water provision:	Up to 120 L max. (In standard size cabinet)
Extinguishing unit:	IFEX CAFS
Extinguishing agent additive:	AFFF foaming agent with dosing pump assembly
Closure element:	Roller shutter, bottom-up opening

Further options on request